

## QY-F5101-OF

### Products Features:

1. Industrial-Grade Open Frame Touch Monitor
2. 10.1 inch LED Screen, Resolution: 1280\*800
3. Support Capacitive and Resistive Touch Screen
4. HDMI+VGA or DVI+VGA Two Type Display Ports Combinations
5. USB or RS-232 Touch Port
6. DC 12V Power Input
7. -20°C~60°C Temperature Can Keep 24/7 Work Stably
8. Front Panel IP65 Water proof



## 1.Specification:

<b>Model</b>	<b>QY-F5101-OF</b>	
<b>Display Port</b>	<b>HDMI+VGA</b>	
	<b>DVI+VGA</b>	
<b>Touch Port</b>	<b>USB (DB9 Type. Default)</b>	
	<b>RS-232 (DB9 Type)</b>	
<b>Screen Size</b>	<b>10.1 inch TFT LED Screen, 16:9 Size</b>	
<b>Resolution</b>	<b>1280*800</b>	
<b>Brightness</b>	<b>350 nits</b>	
	<b>Support optional 500 / 700 nits</b>	
<b>Largest Colorful</b>	<b>16M</b>	
<b>Touch Screen Type</b>	<b>Capacitive</b>	<b>Resistive</b>
<b>Light Transmittance</b>	<b>More than 95%</b>	<b>More than 95%</b>
<b>Touch Life</b>	<b>50 million times</b>	<b>35 million times</b>
<b>Response Time</b>	<b>&lt; 5ms</b>	<b>&lt; 5ms</b>
<b>Touch Hardness</b>	<b>6 Mohs</b>	
<b>Menu</b>	<b>None</b>	

## 2. Device Specification:

<b>Power Input</b>	<b>DC 12V (Support Optional DC 9-36V Wide Voltage Power Module)</b>
	<b>Support Auto-Start</b>
	<b>2 Pin Phoenix Terminal Type DC Plug</b>
<b>Working Temperature</b>	<b>-20°C~60°C, Support 24/7 Working</b>
<b>Structure</b>	<b>Fully Enclosed Aluminum Alloy Material</b>
<b>Heat Dissipation</b>	<b>Fanless Design, Conduction Heat Dissipation</b>
<b>Installation</b>	<b>Desktop / Embedded / Wall Mount</b>
<b>Size</b>	<b>262.8mm*185.7mm*51.7mm</b>
<b>Protection</b>	<b>Front Panel IP65 Water Proof</b>

## 3. Ordering Information:

Model	Display	Touch Port	Touch Screen Type	Power
QY-F5101-OF	HDMI+VGA	USB	Capacitive Resistive	DC 12V
		RS-232		
	DVI+VGA	USB		
		RS-232		

## 4. Package List:

Adapter	1*12V 5A Adapter
Power Cable	1*Power Cable
Mount Clamp	4*Mount Clamp

## 5. Dimensions:

